

Stacked Washer-Extractor/Tumble Dryers

		SST30		SST50	
		Washer-Extractor	Tumble Dryer	Washer-Extractor	Tumble Dryer
Control Option		Quantum Touch		Quantum Touch	
Capacity - lb (kg)		30 (13) x 2		50 (23) x 2	
Overall Width - in (mm)		31.4 (797)		34.4 (875)	
Overall Depth - in (mm)		45.5 (1152)		51.3 (1302)	
Overall Height - in (mm)		79.7 (2023)		84.3 (2141)	
Cylinder Diameter - in (mm)		24.0 (610)	30.0 (762)	26.3 (668)	33.0 (838)
Cylinder Depth - in (mm)		16.0 (406)	26.0 (660)	20.3 (515)	30.0 (762)
Cylinder Volume - cu. ft (liters)		4.2 (119)	10.6 (300)	6.3 (178)	14.8 (419)
Reversing Cylinder		-	Standard	-	Standard
Door Opening Size - in (mm)		14.3 (363)	22.6 (574)	16.3 (414)	26.9 (683)
Door Bottom to Floor - in (mm)		14.0 (356)	51.3 (1303)	14.6 (370)	52.3 (1328)
Water Inlet Connection - in (mm)		2 x 0.75 (19)	-	2 x 0.75 (19)	-
Drain Diameter - in (mm)		1 x 3 (76)	-	1 x 3 (76)	-
Drain Height to Floor - in (mm)		4.3 (108)	-	4.5 (115)	-
Heat Input Power - Btu/hr (kW, Mj/hr.)		-	73,000 (21.4, 77.0)	-	95,000 (27.8, 100)
Gas Connection - in		-	1/2 NPT	-	1/2 NPT
Air Outlet - in (mm)		-	8.0 (200) Elliptical	-	10.0 (250) Elliptical
Airflow - cfm (l/sec)		-	400 (190)	-	600 (285)
Motor - HP (kW)	Fan	-	0.5 (0.4)	-	0.5 (0.4)
	Drive	1 (0.75)	0.3 (0.2)	2 (1.5)	0.5 (0.4)
Total # of Speeds		9	-	9	-
Cylinder Speeds - RPM (G-Force)	Gentle	34 (0.4)	-	33 (0.4)	-
	Wash	48 (0.8)	-	46 (0.8)	-
	Distribution	86 (2.5)	-	82 (2.5)	-
	Very Low	282 (27)	-	269 (27)	-
	Low	485 (80)	-	464 (80)	-
	Medium	542 (100)	-	518 (100)	-
	High	606 (125)	-	579 (125)	-
	Very High	664 (150)	-	635 (150)	-
	Ultra High	766 (200)	-	733 (200)	-
Electrical Specs - amps	X	200-240V/50/60/1/3		15	10
Shipping Dimensions Approx. - in (mm)	Width	34.5 (876)		35.5 (902)	
	Depth	47.0 (1194)		54.0 (1372)	
	Height	83.0 (2108)		89.0 (2261)	
Net Weight - lb (kg)		770 (349)		910 (413)	
Shipping Weight - lb (kg)		787 (357)		930 (422)	
Agency Approvals		UL _c _{us} CSA		UL _c _{us} CSA	

For the most accurate information, the installation guide should be used for all design and construction purposes.
 Due to continuous product improvements, design and specifications subject to change without notice.
 The quality management systems of Alliance Laundry Systems are registered to ISO 9001.
 The washer and dryer units can be separated and reassembled if necessary.